

# OP710 SI

## Multichannel Optical Power Meter

### Overview

#### Multichannel Optical Power Meter

The **OP710 SI** offers an economical approach for optical power measurement applications where multiple channels are needed. Unlike other systems this instrument is built up with individual power meters allowing for unparalleled simultaneous data acquisition over all channels.



Model OP710 Multichannel Optical Power Meter

The **OP710SI** is available starting at 4 up to 24 channels and is configured with a Silicon (SI) detector and the adapter system. With the rack mount option, multiple instruments can be combined and configured for even higher channel counts.

### Features

#### High precision fiber optic power measurement

- Up to 24 channels of precision optical power measurement,
- +10dBm..-80dBm measurement range, 840nm ... 1700nm wavelength range.
- Great measurement resolution of 0.001 dB
- Tight linearity specifications: +/- 0.05dB

#### POF Applications

- The 710SI is equipped with Silicon detectors specifically design to support all POF (plastic optical fiber) applications. To support many POF measurement tasks a variety of connector adapters (MOST, VLink, SMA) are available upon request.

#### Integrated ambient temperature tracking

- The OP710 measures the ambient temperature between -10 °C and +55 °C with a resolution of 0.1 °C.

#### USB powered, plug and play data acquisition

- The OP710 supports data rates up to 0.2MB/s with the appropriate drivers.

	CC = number of channels	OP710-CC-SI	OP710-CC-SI3
Detail Specifications	Individual Channels (other counts available)	4 to 24	4 to 24
	Measurement Range	+3dBm..-60dBm	+10dBm..-60dBm
	Wavelength Range	480nm ..1080nm	
	Selectable Wavelength <sup>1)</sup>	Standard: 650/850/980nm	
	Measurement Resolution (Display)	0.01dBm (absolute) 0.001dB(relative)	
	Measurement Linearity, Relative Accuracy <sup>2)</sup>	0.05dB	
	Data Interface	USB 1.1/2.0 >10 samples/second acquisition rate	
	Operating Temperature Range	0 °C to 50 °C (32 °F to 121 °F)	
	Mechanical Dimension	19" Rack Standard (16.8 x 3.8 x 10")	
	Optical Interface	fixed ST, FC or SC	5/8" adapter (FC/PC included)
Power Supply	Universal AC input: 90VAC to 264VAC, 43Hz.. 63Hz		

Specifications are subject to change, please confirm specific performance characteristics of the product at the time of ordering.

All specifications are valid within temperature range of 18° C to 24°C unless otherwise noted.

1) NIST traceable calibration at -10dBm power level.

2) Linearity for loss <5dB and absolute power within 0 dBm to -65dBm.

3) Linearity for +3dBm to 0dBm, and -65dBm to 72dBm.